

# VALUE FLOODLIGHT





# **Description**

The Value Floodlight is a versatile and durable lighting solution designed to meet the needs of residential, commercial, and industrial areas. With a luminous efficacy of 100 lumens per watt, it provides bright and efficient illumination, ensuring optimal visibility and safety. This floodlight has an impressive lifespan of 36,000 hours @L70, offering long-lasting performance and reducing the need for frequent replacements. Ideal for a wide range of applications, the Value Floodlight is perfect for illuminating stadiums, exhibition centers, parking lots, shopping malls, and building facades. The Value Floodlight is backed by a warranty of 2 years, providing you with peace of mind and assurance of quality.

# **Product Benefits**

Light Uniformity and Sight Advantage
Up to 80% Savings in Energy Cost
Bright, Robust and Durable
Low Maintenance Cost

# **Application Areas**

For Recreational Sports / Residential	
Exhibition Center	
Parking Lots / Shopping Mall	
Accent Lighting / Building Facades	

# **Product Data**

# **General Information**

Driver Included:	Yes
Lifespan:	36,000 hours @ L70
Warranty:	2 Year

# **Luminaire Performance**

Power Consumption:	30W, 50W, 100W, 150W, 200W
Luminous Flux:	3,000 lm, 5,000 lm, 10,000 lm, 15,000 lm, 20,000 lm
Luminous Efficacy (rated):	100 lm/W
Correlated Color Temperature:	3000K, 4000K, 5700K, 6500K
Color Rendering Index (CRI):	>80, >70
Beam Angle:	120°

# **Operating and Electrical**

Input Voltage:	AC85-265V, AC100-265V
Line Frequency:	50 or 60 Hz
Power Factor (Fraction):	>0.9
SPD:	4kV

#### **Temperature**

Operating Temperature:	-20°C – 40°C

#### Controls

Controls:	On/Off	

Web: www.fast-cables.com UAN: 111-000-343



# **Mechanical and Housing**


Housing Material:	Die-cast Aluminium
Optical Cover Material:	Tempered Glass
Finishing:	Powder Coated
Installation:	Bracket Mounted

# **Compliance and Certifications**

Ingress Protection Code:	IP66
Impact Protection Code:	Safety Class I

# **Dimensions**

Power Consumption:	30W / 50W	100W	150W	200W
LxWxH (mm):	247x42x187	297x52x215	373x56x283	435x60x313



# **Head Office:**

192-Y Block, Commercial Area, Phase III, DHA Lahore, Pakistan.

# **Sales Office:**

120-Y Block, Commercial Area, Phase III, DHA Lahore, Pakistan.

